

### 72796T Wall Mount Connection

#### BEFORE YOU BEGIN


All information is based on the latest product information available at the time of publication. Kohler Co. reserves the right to make changes in product characteristics, packaging, or availability at any time without notice.

Please leave these instructions for the consumer. They contain important information.


#### NOTES:

1. Flush the water supply pipes thoroughly to remove debris.
2. An inline water filter must be used with this product.
3. All installations should comply with the relevant requirements of AS/NZS 3500.

#### ROUGH-IN DIMENSIONS




#### INSTALLATION



Before installation, installer must provide G1/2" nipple(1). The nipple should extend 11mm beyond the finished wall. Ensure the gap between the nipple and finished wall is no more than 10mm. The hole's maximum diameter is 41mm in the wall.

Apply tape or thread sealant to G1/2" threads of the nipple.



Flush both water supplies through the nipple for about one minute to remove debris.

Apply a ring sealants around the underside of the escutcheon(2). Install the connection(3) and escutcheon onto the nipple(1). Adjust the connection kit and make sure the outlet(4) downwards. Tighten them by strap wrench.


Press the escutcheon until against the finished wall. Remove any excess sealant.

## CLEANING INSTRUCTIONS

All Finishes: Clean the finish with mild soap and warm water. Wipe entire surface completely dry with clean soft cloth. Many cleaners may contain chemicals, such as ammonia, chlorine, toilet cleaner etc, which could adversely affect the finish and are not recommended for cleaning.

Do not use abrasive cleaners or solvents on Kohler faucets and fittings.

## SERVICE PARTS



\*\*Color code must be specified when ordering.

**NOTE:** For all Asia pacific regions (excluding China) add SP (SPxxxxxx\*\*) in front of the part number when ordering.