


72695T-B4 R8654T-B Wall-Mount Bath Shower Faucet  
72697T-B4 Wall-Mount Shower Only Faucet



\*\*Color code must be specified when ordering.

**NOTE:** For all Asia pacific regions (excluding China) add SP (SPxxxxxx\*\*) in front of the part number when ordering.

72695T-B4 R8654T-B Wall-Mount Bath Shower Faucet  
72697T-B4 Wall-Mount Shower Only Faucet

### BEFORE YOU BEGIN

All information is based on the latest product information available at the time of publication. Kohler Co. reserves the right to make changes in product characteristics, packaging, or availability at any time without notice.

Please leave these instructions for the consumer. They contain important information.

### NOTES:

1. Flush the water supply pipes thoroughly to remove debris.
2. The minimum inlet water pressure for the diverter is 0.05MPa(0.5bar).
3. The highest working pressure for handspray is 0.5MPa(5bar). If it exceeds 0.5MPa(5bar), a pressure reducer is needed. The highest water and environment temperature is 60°C. Please keep handspray, showerhead and the shower arm away from heater, or it may become damaged and cause injury to the user.
4. These products contain natural jade material. Do not contact lipstick and other easy dyeing cosmetics.


### STANDARD APPLICABLE

Special model meets or exceeds the following at date of manufacture: TIS

### OPERATION CONDITION

Lift the handle gently. Turn clockwise for hot water, counter-clockwise for cold water.

### ROUGH-IN DIMENSIONS



72695T-B4 R8654T-B

72697T-B4

## INSTALLATION

### How to Install the Faucet

To perform installation, installer must provide G1/2" female supply fittings(1), spaced 150mm apart and level. The supply fittings should be vertical and not beyond the finished wall. Hot supply pipe must be located on the left.


Install the two offset connectors(2) into the hot and cold supply pipes. Use appropriate thread sealants or thread tape on pipe threads.

Adjust the center-to-center distance between the connectors to 150mm and level. They should extend 28 to 30mm beyond the finished wall. Thread the escutcheons(3) onto the connectors until they are against the finished wall.

Put the washers(5) into the nuts(4), thread the nuts to connectors.

When tighten the nuts, use strap wrench or soft cloth between product and regular wrench to protect the finish.

Connect hose(8) to the faucet outlet(7), and to the handspray(9) with washers(6).



### How to Install the Bracket


Determine a suitable location on the finished wall to install the bracket.

**For the finish with CP:** Take off the locking pin(11) from the bracket(10). Take out the self-tapping screws(12) and anchors(14) from the inside of the bracket by pulling out the plastic sleeve(13).

Mark bracket base mounting hole location on the wall. Drill two holes on the finished wall as required. Press the anchors into the holes and screw the self-tapping screws into the anchors through the sleeve. Tighten them by screwdriver. Align the bulge of the bracket and the slot of the sleeve. Slide the bracket onto the sleeve and insert the locking pin into the hole of bracket and sleeve.

**For the other finish:** Mark bracket base mounting hole locations on the wall according to the dimension. Drill two holes on the finished wall, the holes should match the anchors(15). Install the anchors.

Tighten screws(16) to secure bracket base(17, flat side upward). Put the bracket(18) onto the bracket base and lock by stopper.



## INSTALLATION CHECKOUT

Ensure that all coupling nuts are tight.

Ensure that the handle is in the off position.


Turn on the main water supply, and check for leaks. Repair as needed.

### Bath & Shower Faucet:

Remove the handspray(9) and the aerator(19). Run hot and cold water through the faucet for about a minute to remove any debris. Check for leaks. Remove any debris from the aerator assembly. Shut the faucet off, and reinstall the aerator assembly and handspray.

### Shower Faucet:

Remove the handspray(9). Run hot and cold water through the faucet for about one minute to remove any debris. Check for leaks. Shut the faucet off, and reinstall the handspray.



## CLEANING INSTRUCTIONS

All Finishes: Clean the finish with mild soap and warm water. Wipe entire surface completely dry with clean soft cloth. Many cleaners may contain chemicals, such as ammonia, chlorine, toilet cleaner etc, which could adversely affect the finish and are not recommended for cleaning.

Do not use abrasive cleaners or solvents on Kohler faucets and fittings.