

### SINGLE-HOLE LAVATORY FAUCET K-37301X



#### Features

- Brass construction
- Single-hole mounting
- One-piece, self-contained ceramic disc valve allows both volume and temperature control
- Flexible connections for easy installation
- Includes pop-up drain with lift rod and tailpiece
- 103 mm spout reach
- Lever handle

#### Codes/Standards Applicable

- Specified model meets or exceeds the following:
- TIS 2067-2552


#### Installation Notes

Install this product according to the installation guide.

#### Specified Model

Model	Description	Color/Finished
K-37301X-4	Cuff single-hole lavatory faucet	CP: Polished Chrome

Dimensions are approximate.  
Unit: mm



#### Product Diagram

## คุณลักษณะ

- ผลิตจากทองเหลือง
- ติดตั้งแบบรูก๊อกเดียว
- เซรามิกวาล์ว วาล์วก่อนน้ำเดี่ยวควบคุมทั้งปริมาณน้ำและอุณหภูมิ
- ติดตั้งด้วยสายน้ำดี ทำให้ติดตั้งได้ง่าย
- พร้อมสื่อดูด่างแบบปั๊บบัฟ
- ระยะจากกึ่งกลางตัวก๊อกถึงกึ่งกลางปากก๊อก 103 มม.
- มือบิดแบบก้านโยก

## มาตรฐาน

คุณสมบัติตามมาตรฐาน

- มอก. 2067-2552

## ข้อสังเกตสำหรับการติดตั้ง

ติดตั้งผลิตภัณฑ์โดยใช้คู่มือแนะนำการติดตั้ง

## ก๊อกผสมอ่างล้างหน้ารูเดี่ยวแบบก้านโยก K-37301X




## รุ่นผลิตภัณฑ์

รุ่น	ชื่อผลิตภัณฑ์	สี/วัสดุเคลือบผิว
K-37301X-4	ก๊อกผสมอ่างล้างหน้ารูเดี่ยวแบบก้านโยก รุ่นคัพ	สี/วัสดุเคลือบผิว CP: สีโครมเงา

ขนาดระยะแสดงค่าโดยประมาณ

หน่วย: มม.



ภาพแสดงผลิตภัณฑ์